




V 209
Escala 1:50




V 210
Escala 1:50




V 212
Escala 1:50




V 213
Escala 1:50




V 214
Escala 1:50




V 215
Escala 1:50




V 216
Escala 1:50




V 217
Escala 1:50




V 218
Escala 1:50




V 219
Escala 1:50



V 220
Escala 1:50



V 221
Escala 1:50



Elemento	Pos.	Diam.	Q.	Dob./Reta (cm)	Comp. (cm)	Total (cm)	CA-50-A (kg)	CA-60-B (kg)
V 212								
1	012.5	2	15	780	800	1580	15.7	
2	012.5	2	15	780	795	1580	15.6	
3	012.5	2	15	780	800	1580	15.7	
4	012.5	2	15	780	800	1580	15.7	
5	012.5	2	15	780	800	1580	15.7	
6	012.5	2	15	780	800	1580	15.7	
7	012.5	2	15	780	800	1580	15.7	
8	012.5	2	15	780	800	1580	15.7	
9	012.5	2	15	780	800	1580	15.7	
10	012.5	2	15	780	800	1580	15.7	
11	010	3	15	168	180	348	3.5	
12	06.3	118	405	455	1351	15458	36.2	
Total 10%							156.8	
V 213								
13	012.5	4	19	780	810	1590	32.1	
14	012.5	2	15	780	795	1580	15.6	
15	012.5	2	15	780	800	1580	15.7	
16	010	3	15	168	180	348	3.5	
17	012.5	2	15	780	800	1580	15.7	
18	012.5	2	15	780	800	1580	15.7	
19	012.5	2	15	780	800	1580	15.7	
20	012.5	2	15	780	800	1580	15.7	
21	010	3	15	168	180	348	3.5	
22	012.5	2	15	780	800	1580	15.7	
23	010	3	15	168	180	348	3.5	
24	08	12	775	775	775	2325	24.8	
25	06.3	40	219	219	8777	21.7		
26	06.3	87	131	131	8777	21.7		
Total 10%							285.7	
V 214								
27	010	2	12	225	12	248	48	3.1
28	010	2	12	225	12	248	48	3.1
29	05	12	94	1128				1.8
Total 10%							6.8	
V 215								
30	012.5	2	15	1035	1000	2100	20.6	
31	012.5	2	15	780	800	1580	15.7	
32	012.5	2	15	780	800	1580	15.7	
33	010	3	15	168	180	348	3.5	
34	012.5	2	15	780	800	1580	15.7	
35	010	3	15	168	180	348	3.5	
36	010	3	15	168	180	348	3.5	
37	012.5	2	15	780	800	1580	15.7	
38	08	12	775	775	775	2325	24.8	
39	06.3	40	219	219	8777	21.7		
40	06.3	87	131	131	8777	21.7		
Total 10%							163.2	
V 216								
41	012.5	2	15	1035	1000	2100	20.6	
42	012.5	2	15	780	800	1580	15.7	
43	012.5	2	15	780	800	1580	15.7	
44	012.5	2	15	780	800	1580	15.7	
45	010	3	15	168	180	348	3.5	
46	012.5	2	15	780	800	1580	15.7	
47	010	3	15	168	180	348	3.5	
48	010	3	15	168	180	348	3.5	
49	012.5	2	15	780	800	1580	15.7	
50	08	12	775	775	775	2325	24.8	
51	06.3	40	219	219	8777	21.7		
52	06.3	87	131	131	8777	21.7		
Total 10%							164.8	
V 217								
53	012.5	2	15	780	800	1580	15.7	
54	012.5	2	15	780	795	1580	15.6	
55	012.5	2	15	780	800	1580	15.7	
56	012.5	2	15	780	800	1580	15.7	
57	010	3	15	168	180	348	3.5	
58	010	3	15	168	180	348	3.5	
59	012.5	2	15	780	800	1580	15.7	
60	012.5	2	15	780	800	1580	15.7	
61	012.5	2	15	780	800	1580	15.7	
62	010	3	15	168	180	348	3.5	
63	010	3	15	168	180	348	3.5	
64	012.5	2	15	780	800	1580	15.7	
65	010	3	15	168	180	348	3.5	
66	010	3	15	168	180	348	3.5	
67	010	3	15	168	180	348	3.5	
68	06.3	118	405	455	1351	15458	36.2	
Total 10%							156.8	
V 218								
69	012.5	4	19	780	785	1565	31.2	
70	012.5	2	15	780	800	1580	15.7	
71	010	3	15	168	180	348	3.5	
72	012.5	2	15	780	800	1580	15.7	
73	012.5	2	15	780	800	1580	15.7	
74	012.5	2	15	780	800	1580	15.7	
75	012.5	2	15	780	800	1580	15.7	
76	010	3	15	168	180	348	3.5	
77	06.3	118	405	455	1351	15458	36.2	
Total 10%							156.4	
V 219								
78	012.5	2	15	780	800	1580	15.7	
79	012.5	4	19	780	810	1590	32.1	
80	012.5	2	15	780	800	1580	15.7	
81	010	3	15	168	180	348	3.5	
82	012.5	2	15	780	800	1580	15.7	
83	010	3	15	168	180	348	3.5	
84	010	3	15	168	180	348	3.5	
85	012.5	2	15	780	800	1580	15.7	
86	010	3	15	168	180	348	3.5	
87	010	3	15	168	180	348	3.5	
88	08	12	775	775	775	2325	24.8	
89	06.3	40	219	219	8777	21.7		
90	06.3	87	131	131	8777	21.7		
Total 10%							197.2	
V 220								
91	012.5	2	15	780	800	1580	15.7	
92	012.5	2	15	780	800	1580	15.7	
93	010	3	15	168	180	348	3.5	
94	010	3	15	168	180	348	3.5	
95	012.5	2	15	780	800	1580	15.7	
96	012.5	2	15	780	800	1580	15.7	
97	08	12	775	775	775	2325	24.8	
98	06.3	40	219	219	8777	21.7		
99	06.3	87	131	131	8777	21.7		
Total 10%							197.2	
V 221								
100	012.5	2	15	784	800	1584	16.0	
101	010	3	15	168	180	348	3.5	
102	010	3	15	168	180	348	3.5	
103	010	3	15	168	180	348	3.5	
104	06.3	27	149	149	6023	9.8		
Total 10%							45.7	
V 209								
105	010	3	26	779	805	1584	25.3	
106	012.5	2	15	780	800	1580	15.7	
107	010	3	15	168	180	348	3.5	
108	010	3	15	168	180	348	3.5	
109	010	3	15	168	180	348	3.5	
110	010	3	15	168	180	348	3.5	
111	010	3	15	168	180	348	3.5	
112	010	3	15	168	180	348	3.5	
113	010	3	15	168	180	348	3.5	
114	010	3	15	168	180	348	3.5	
115	012.5	2	15	780	800	1580	15.7	
116	012.5	2	15	780	800	1580	15.7	
117	010	3	15	168	180	348	3.5	
118	010	3	15	168	180	348	3.5	
119	010	3	15	168	180	348	3.5	
120	06.3	40	219	219	8777	21.7		
Total 10%							250.4	
V 210								
121	010	2	12	238	12	263	526	3.3